

DPM-2550 B

Digital Selective Remote Microphone Unit



EN 54 16

APPLICATION

- Public Address and Voice Alarm
- Background Music
- Audio Visual

AREA OF USE

- Health
- Education
- Retail
- Hospitality
- Stadiums
- Transportation
- Theme parks
- Military

OVERVIEW

The Digital-Selective-Remote-Microphone-Unit DPM-2550 B is a microcontroller-supported fully digital microphone station with bidirectional digital transmission of data signal. The function assignment of all memory keys of the call station is freely programmable including numeric keypad function.


Monitoring according to EN54-16 can be activated with the software license. There are 8 function keys, a 12-key keypad block for individual or group calls, one covered alarm button and a large, user-friendly talk button are available.

The "+" and "-" function keys can be used to change the sound carrier volume, the sensitivity of the sound carrier input, the microphone volume and the characteristics of the compressor and gate functions. The illuminated graphic display shows the selected areas in plain text.

In addition, status messages from the plant system can be

displayed here.

The DPM-2550 B features high-performance A/D and D/A converters with 128x oversampling for pristine reproduction of speech and music. The input and output channel gain is from 0 to 59.9 dB and 0 to 63.5 dB adjustable in 0.5 dB increments. A compressor/gate function (individually adjustable), as well as automatic volume adjustment of the microphone input using automatic gain control (AGC) to ensure maximum intelligibility of the announcements of the different speakers is an built-in feature. On top of that, there is a possibility to connect an external sound carrier device to the built-in stereo cinch sockets as an option. Up to 10 DPM-2551 A digital remote microphone extension modules or up to 5 DPM-2552 A digital remote microphone extension modules can be attached to a DPM-2550 B.



TECHNICAL DATA

Microphone	Electret Cardioid
Gooseneck length	280 mm
Alarm buttons	2, illuminated, covered
Keyboard block	12 + 8 (15+5)
Talk button	1
Internal display	64 x 128 pixels with backlight
Supervision	The link with DPM controllers and capsule of MIC.
Frequency response	(-3dBu) at 200 – 15,000 Hz
THD	Less than 1% @ 1 KHz
Power supply	24 V DC via RJ45 port
Current consumption	125 mA (max.)
System connection	RJ-45
Operating temperature	-5 C° to + 50 C°
Dimensions (W x H x D)	250 x 45 x 196 mm
Weight	1.25 kg

All rights reserved.

Information contained in this document is believed to be accurate, however no representation or warranty is given and Audemo-systems in Germany assumes no liability with respect to the accuracy of such information.

AUDEMO - SYSTEMS GmbH (Headquarter)

Schatzbogen 62 81829 Munchen
Tel.: +49 (0) 89 1 4 56 78 47 - 0, Fax: +49 (0) 89 1 4 56 78 47- 2900
info@audemo-systems.de, www.audemo-systems.de



Member of the ZVEI - Central Association
for the Electrical Engineering and Electrical
Industry eV Safety Association

